

Electrical Output	Continuous	Intermittent
Rated Output	20 kW (100%)	24 kW (120%)
Output Voltage	120/240V - Single Phase 208V, 240V, or 480V - Three Phase	
Output Frequency	60 Hz (specs listed here) or 50 Hz (consult factory)	
System Output*		
CHP Performance		
Electrical Output (BTU/h)	68,240	81,888
Nominal Hydronic Heat Output (BTU/h)	33,761	35,923
Fuel Consumption (BTU/h)**	176,113	184,711
Electrical Efficiency	39%	43%
Max Heat Recovery Efficiency	19%	19%
Total Max CHP Efficiency	58%	63%
Hydronic Parameters		
Outlet Water Temperature (optional)***	Up to 80°C / 175°F	
Other		
Engine	Internal Combustion	
Fuel Type	Natural Gas / Propane	
Fuel Pressure	5 - 25" H2O (0.18-0.90 PSI)	
Sound Level	58 dBA / 62 dBA with radiator fan on	
Communications	Ethernet - Remote system monitoring / Networking	
Dimensions - in. (L x W x H)	79" x 35" x 76"	
Weight	1,020 lbs. (463 kg)	
Warranty	2 Years	

Specifications subject to change without notice.

*System output is based on 480V Operation

**Lower Heating Value

***Requires auxiliary circulating pump